

## *ODTR Launch Fiber Cable*



### **General Description:**

Baudcom provides high performance Launch Fiber Cable (Launch Leads) with anti-corrosion box. SC/FC/LC connectors are selectable as well as the UPC and APC polishing mode. Designed to aid in the testing of fiber optic cable when using an OTDR. The OTDR Launch Fiber box is used with Optical Time Domain Reflectometers (OTDR's) to help minimize the effects of the OTDR's launch pulse on measurement uncertainty. Available in many different configurations and fiber lengths. Composed with high density anti-corrosion material outer box, highly enhance the environment suitability and durability. This product is definitely your good partner in Fiber Optic Testing Projects.

### **Features:**

1. Compact and ruggedized, easy to carry
2. Excellent waterproof and dustproof performance

3. Auto Purge Valve for changes in altitude and temperature
4. Non-metal construction will not corrode or conduce electricity

### Specifications:

Dimension	23.8(L) x 14.1(W) x 6.7(H)cm
Fiber Type	G.657A/G.652D (MM can be customized)
Typical Loss	<0.5dB @ 1310nm for 1,000 meters
Connector Type	FC/SC/LC selectable
Polishing Type	APC/UPC selectable
Box Material	SR Polypropylene
Color	yellow
Weight	0.75kg / 0.35kg (without fiber)
Operating Temperature	-40~+55°C

